


Stop Valves



H	G	4211	32	23
<b>SERIES NUMBER</b>	<b>MOUNTING</b> G : SUB-PLATE MOUNTING T : THREADED CONNECTIONS F : FLANGED CONNECTIONS	<b>SERIES NUMBER</b>	<b>VALVE SIZE</b>	<b>DESIGN NUMBER (AS C11-03)</b>

Model			Port	Max. Operated Pressure (kgf/cm <sup>2</sup> )	Rated Flow
SUB-PLATE MOUNTING	THREADED CONNECTIONS	FLANGED CONNECTIONS			
HG-4211-10-23	HT-4211-10-23	HF-4211-10-23	3/8"	315	30
-	HT-4211-15-23	HF-4211-15-23	1/2"		60
HG-4211-20-23	HT-4211-20-23	HF-4211-20-23	3/4"		100
-	HT-4211-25-23	HF-4211-25-23	1"		220
HG-4211-32-23	HT-4211-32-23	HF-4211-32-23	1-1/4"		280
-	-	HF-4211-40-23	1-1/2"		500
-	-	HF-4211-50-23	2"		800

Manually Operated Directional Valves



DM	T	03	3	C	6
<b>SERIES NUMBER</b>	<b>MOUNTING</b> G : SUB-PLATE MOUNTING T : THREADED CONNECTIONS	<b>VALVE SIZE</b> 03 : 3/8" 04 : 1/2" 06 : 3/4" 10 : 1-1/4"	<b>NUMBER OF VALVE POSITION</b> 2 : 2 POSITION 3 : 3 POSITION	<b>CENTERED LOCKING</b> C : SPRING LOCKING D : BALL LOCKING	<b>SPOOL TYPE</b>

Model		Max. Operated Pressure (kgf/cm <sup>2</sup> )	Back Pressure (kgf/cm <sup>2</sup> )	Max. Flow (l/min)	Weight (kg)	
THREADED CONNECTIONS	SUB-PLATE MOUNTING					
DMT-03- <del>X</del>	DMG-03- <del>X</del>	250	100	50	4.5	4
DMT-04- <del>X</del>				100	7.0	
DMT-06- <del>X</del>			140	180	11.5	
DMT-10- <del>X</del>				300	22.9	

Cam Operated Directional Valve



DC	G	02	2BC	10	R
<b>SERIES NUMBER</b>	<b>MOUNTING</b> G : SUB-PLATE MOUNTING	<b>VALVE SIZE</b> 02 : 20 l/min	<b>VALVE TYPE</b> 2BC 2BO 2B2 2B2S	<b>DESIGN NUMBER</b>	<b>ROLLER POSITION</b> R : LEFT S : RIGHT Y : UPSIDE

Model	Max. Operated Pressure (kgf/cm <sup>2</sup> )	Max. Back Pressure (kgf/cm <sup>2</sup> )	Max. Flow (l/min)	Weight (kg)
DCG-02- <del>X</del> -10- <del>X</del>	210	70	30	1.4
DCG-02- <del>X</del> -20- <del>X</del>	210	70	30	1.4

