


Stop Valves



H	G	4211	32	23
SERIES NUMBER	MOUNTING G : SUB-PLATE MOUNTING T : THREADED CONNECTIONS F : FLANGED CONNECTIONS	SERIES NUMBER	VALVE SIZE	DESIGN NUMBER (AS C11-03)

Model			Port	Max.Operated Pressure (kgf/cm ²)	Rated Flow
SUB-PLATE MOUNTING	THREADED CONNECTIONS	FLANGED CONNECTIONS			
HG-4211-10-23	HT-4211-10-23	HF-4211-10-23	3/8"	315	30
-	HT-4211-15-23	HF-4211-15-23	1/2"		60
HG-4211-20-23	HT-4211-20-23	HF-4211-20-23	3/4"		100
-	HT-4211-25-23	HF-4211-25-23	1"		220
HG-4211-32-23	HT-4211-32-23	HF-4211-32-23	1-1/4"		280
-	-	HF-4211-40-23	1-1/2"		500
-	-	HF-4211-50-23	2"		800

Manually Operated Directional Valves



DM	T	03	3	C	6
SERIES NUMBER	MOUNTING G : SUB-PLATE MOUNTING T : THREADED CONNECTIONS	VALVE SIZE 03 : 3/8" 04 : 1/2" 06 : 3/4" 10 : 1-1/4"	NUMBER OF VALVE POSITION 2 : 2 POSITION 3 : 3 POSITION	CENTERED LOCKING C : SPRING LOCKING D : BALL LOCKING	SPOOL TYPE

Model		Max.Operated Pressure (kgf/cm ²)	Back Pressure kgf/cm ²	Max.Flow (l/min)	Weight (kg)	
THREADED CONNECTIONS	SUB-PLATE MOUNTING					
DMT-03-	DMG-03-	250	100	50	4.5	4
DMT-04-			140	100	7.0	
DMT-06-				180	11.5	
DMT-10-				300	22.9	

Cam Operated Directional Valve



DC	G	02	2BC	10	R
SERIES NUMBER	MOUNTING G : SUB-PLATE MOUNTING	VALVE SIZE 02 : 20 l/min	VALVE TYPE 2BC 2BO 2B2 2B2S	DESIGN NUMBER	ROLLER POSITION R: LEFT S: RIGHT Y: UPSIDE

Model	Max.Operated Pressure (kgf/cm ²)	Max.Back Pressure kgf/cm ²	Max.Flow (l/min)	Weight (kg)
DCG-02--10-	210	70	30	1.4
DCG-02--20-	210	70	30	1.4

