

YT20H

Seamless Steel Honed Tube



ID (mm Ø)	OD (mm Ø)	Working Pressure (kg/cm ²)	ID (mm Ø)	OD (mm Ø)	Working Pressure (kg/cm ²)	ID (mm Ø)	OD (mm Ø)	Working Pressure (kg/cm ²)
18	31	752	75	95	278	135	160	193
20	30	520	76.2	88.9	174	140	153	97
25	35	416	80	90	130	140	160	149
30	36	208	80	92	156	140	165	186
30	40	347	80	95	195	140	170	223
32	42	325	80	100	260	145	170	180
35	45	298	82.55	98	194	150	160	70
38.1	50.8	347	85	95	123	150	163	91
40	45	130	85	100	184	150	168	125
40	46	156	90	100	116	150	170	139
40	48	208	90	105	174	150	175	174
40	50	260	90	110	232	150	180	208
40	55	390	95	110	165	152.4	178	175
45	55	232	95	115	219	160	172	78
45	60	347	100	107	73	160	180	130
50	55	104	100	110	104	160	185	163
50	57	146	100	114	146	160	190	196
50	58	167	100	116	167	165	190	158
50	60	208	100	120	208	170	190	123
50	65	312	100	125	260	170	195	153
50	70	416	100	130	312	175	190	90
50.8	63.5	260	100	135	364	177.8	203	148
55	65	190	101.6	118	168	180	196	93
55	70	284	105	120	149	180	202	128
60	70	174	105	125	199	180	210	174
60	72	208	110	125	142	180	216	208
60	75	260	110	130	190	180	220	232
60	80	347	110	135	237	183	205	125
63	68	83	115	130	136	185	220	197
63	71	133	115	135	181	190	220	164
63	73	166	120	132	104	200	216	84
63	76	215	120	135	130	200	232	167
63	80	281	120	140	174	200	242	219
63.5	76.2	208	120	145	217	203.2	228.5	130
65	75	160	125	137	100	220	273	250
65	80	240	125	140	125	225	254	135
65	85	320	125	145	167	250	268	75
70	80	149	125	150	208	250	299	204
70	85	223	127	146	156	300	318	63
70	90	298	130	142	96	300	351	174
75	85	139	130	150	160	350	420	208
75	90	208	130	153	184			

Remark

- External Diameter : Ø 30 – 420 mm
- Internal Diameter : Ø 18 – 350 mm
- Material : JIS SKM 13C / SAE 1020 / DIN ST52 (Also offer welded honed tube: DIN ST 52.3; other specification can be customized.)
- ID Accuracy : H7, H8, H9 (Please Consult Page 10)
- Internal Roughness : Ra 0.4 – 0.8
- Standard Length : 3 – 8 M
- Special Length : 13 M